

# 2N® INDOOR TALK

ELEGANT ANSWERING UNIT WITH HD SOUND

The design of the 2N® Indoor Talk answering unit will suit every flat or home. The aesthetic appearance of this product was achieved by using a glass surface and striking backlighting of its icons. However, we placed particular emphasis on selecting the highest-quality audio components in order to achieve a high-quality sound. This means you can talk to visitors outside as if they were standing right next to you. Invite them in and press the icon to open the door from the comfort of your home.



- **Luxury design and materials**
- **Modification to your requirements**
- **HD quality sound with high volume**
- **Precision installation box**
- **Concierge call**
- **Simple upgrade to a video communicator**

## VARIANTS



### BLACK

91378401



### WHITE

91378401WH

## TECHNICAL PARAMETERS

### Power supply

Type	10 to 30 V, up to 12 W or PoE 802.3af
Recommended power supply	12 V / 1 A
Reverse polarity protection	yes

### User interface

Controls	7 capacity buttons with RGB LED backlighting
Operation	Press and hold the RESET button to restore factory settings, 3 LED diodes indicating status

### Audio

Microphone	integrated
Speaker	integrated, 2W
Induction loop output	600 mV RMS

### Interface

LAN	10/100BaseT, RJ-45; Cat5e or better
Socket	for doorbell connection
Type of input	switch contact (button/relay)
Contact type	normally open (NO)
Contact parameters	up to 50 V / 5 mA, DC

### Mechanical properties

Dimensions (W x H x D)	185 x 128 x 48.2 mm
Weight	387 g
Operating temperature	0 to 50 °C
Relative operating humidity	10 to 90 % (non-condensing)
Storage temperature	-20 to 70 °C
Recommended altitude	0 - 2000 m